

»»» EXPANDED RANGE »»»

From .33 HP
up to 5 HP



» **Product Range**

Standard: .33HP to 5HP

Deluxe: 1.5HP to 5HP

CSCR: .33HP to 1HP

» **Enclosure**

NEMA Type 3R

Gray Epoxy coated

18 Gauge Steel Construction

» **Benefits**

Pull Handle Disconnect

Safety Shields

UL Recognized Mallory Start Capacitor

UL Recognized General Electric
Voltage Relay

Progressive knockouts

.33HP to 1HP PumpSaver ready

GRUNDFOS CONTROL BOX SA-SPM5

>>> **Quality and Control** >>>



Standard – 0.33 HP to 1 HP

Motor HP	Voltage	Width	Depth	Height	Part Number
0.33	115	6.5"	3.5"	10.75"	91126150
0.33	230	6.5"	3.5"	10.75"	91126151
0.5	115	6.5"	3.5"	10.75"	91126152
0.5	230	6.5"	3.5"	10.75"	91126153
0.75	230	6.5"	3.5"	10.75"	91126154
1	230	6.5"	3.5"	10.75"	91126155

Run Cap – 0.33 HP to 1 HP

.33 CSCR	115	7.5"	4.5"	11.75"	91126206
.33 CSCR	230	7.5"	4.5"	11.75"	91126207
.5 CSCR	115	7.5"	4.5"	11.75"	91126208
.5 CSCR	230	7.5"	4.5"	11.75"	91126209
.75 CSCR	230	7.5"	4.5"	11.75"	91126210
1 CSCR	230	7.5"	4.5"	11.75"	91126211

Standard and Deluxe – 1.5 HP to 5 HP

1.5 STD	230	9.0"	4.5"	13.0"	91126212
1.5 DLX	230	9.0"	4.5"	13.0"	91126213
2 STD	230	9.0"	4.5"	13.0"	91126214
2 DLX	230	9.0"	4.5"	13.0"	91126215
3 STD	230	9.0"	4.5"	16.25"	91126216
3 DLX	230	9.0"	4.5"	16.25"	91126217
5 STD	230	9.0"	4.5"	16.25"	91126218
5 DLX	230	9.0"	4.5"	16.25"	91126219

*All models are single phase, 60 Hz

L-CB-SL-001 4/05 (US)